borg& overström





A design like no other

The b5 range straddles the line between high-end functionality and ultra-modern design. The unique streamlined design of this range will bring sophistication to any environment.



Power requirements Hertz 50/Volts 220-240 Max power consumption Chilled & Ambient 100W Chilled, Ambient & Sparkling 140W Chilled, Ambient & Hot 900W Chilled, Hot & Sparkling 940W

Chilled temperature

Min 2°C/Max 11°C Hot temperature Max 92°C Throughput litres per hour Chilled 22/Hot 6 **Dimensions** Floorstanding Dispense height WxDxH 520x415x1310mm 250mm

- Key Features Optimum height for interaction Fully open lit dispense area Shrouded faucet for hygienic protection
- Compact alarmed drainage system
 Built in leak detector

Available accessories

- Wall Bracket Set
- Sparkling Refill (CO₂ E290)
 CO₂ Regulator with Gauge
 Sanitisation Kit
 Install Kit with Filter

- Blue Tint Cups





b5 Models

Direct Chill, Floorstanding, Chilled, Ambient—101521 Direct Chill, Floorstanding, Chilled, Ambient, Sparkling—101531 Direct Chill, Floorstanding, Chilled, Ambient, Hot—101541 Direct Chill, Floorstanding, Chilled, Hot, Sparkling—101551

Water system



Direct Chill

Borg & Overström Direct Chill utilises innovative technology to chill water instantly. We recommend this system for more demanding environments because of its optimum dispense performance and unrivalled hygienic qualities. Superior to the gravity fed Reservoir system, Direct Chill technology chills water on demand for the ultimate drinking experience.



Call us: 01823 698953 Email us: info@mastervend.co.uk Visit us: www.mastervendsw.co.uk

Ref: 838117 Version: 13012015